Revision Number: 008.0 Issue date: 12/19/2017

PRODUCT AND COMPANY IDENTIFICATION

Product name: **DAVLYN 57** IDH number: 2279470

Product type: Adhesive Restriction of Use: Region: **United States** None identified

Company address: Contact information: Davlyn LLC Telephone: +1 (651) 484-3660

MEDICAL EMERGENCY Phone: Poison Control Center 302 Ansin Blvd Hallandale Beach FL 33179

1-877-671-4608 (toll free)

TRANSPORT EMERGENCY Phone: CHEMTREC

1-800-424-9300 (toll free)

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HIGHLY FLAMMABLE LIQUID AND VAPOR. DANGER:

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

CAUSES SKIN IRRITATION.

CAUSES SERIOUS EYE IRRITATION.

MAY CAUSE DROWSINESS OR DIZZINESS. SUSPECTED OF CAUSING GENETIC DEFECTS.

SUSPECTED OF CAUSING CANCER.

SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD. MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR

REPEATED EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	2
SKIN IRRITATION	2
EYE IRRITATION	2A
GERM CELL MUTAGENICITY	2
CARCINOGENICITY	2
REPRODUCTIVE TOXICITY	2
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	2
ASPIRATION HAZARD	1





Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been

read and understood. Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment. Use nonsparking tools. Take action to prevent static discharges. Do not breathe vapors, mist, or

spray.

Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, clothing, eye and face protection.

Response: IF SWALLOWED: Immediately call a physician or poison control center. If on skin (or hair):

Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. Do NOT induce vomiting. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. In case of fire: Use foam, dry

chemical or carbon dioxide to extinguish.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place.

Keep cool. Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Heptane, branched, cyclic and linear	426260-76-6	15 - 40	
2-Propanol	67-63-0	5 - 30	
Ethyl acetate	141-78-6	5 - 20	
Xylenes	1330-20-7	1 - 10	
Toluene	108-88-3	1 - 10	
Vinyl acetate	108-05-4	1 - 10	

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. Get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. Get medical attention.

Check for and remove any contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

water, also under the eyelids, for at least 15 minutes. Get medical attention.

If material is ingested, immediately contact a physician or poison control center. DO NOT induce vomiting unless directed to do so by medical

personnel. If vomiting occurs, prevent aspiration by keeping the patient's head

below the knees. Never give anything by mouth to an unconscious person.

See Section 11.

Symptoms:

5. FIRE FIGHTING MEASURES

Extinguishing media: Use extinguishing measures appropriate to local circumstances and the

surrounding environment. Water spray (fog), foam, dry chemical or carbon

dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. Isolate area. Keep unnecessary personnel away.

Unusual fire or explosion hazards: Vapors may accumulate in low or confined areas, travel considerable distance

to source of ignition, and flash back. Closed containers may rupture (due to

build up of pressure) when exposed to extreme heat.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Do not allow material to

contaminate ground water system.

Isolate area. Keep unnecessary personnel away. Eliminate all ignition

Clean-up methods: sources (flames, hot surfaces, and sources of electrical, static or frictional

sources (flames, hot surfaces, and sources of electrical, static or frictional sparks). Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered metal containers for recovery or disposal, or remove with inert absorbent. Use only non-sparking tools. Place absorbent diking materials in covered metal containers for disposal. Prevent contamination of sewers, streams and groundwater with spilled material or used absorbent.

7. HANDLING AND STORAGE

Handling: Make sure containers are properly grounded before use or transfer of material.

Keep container closed. Do not breathe gas/fumes/vapor/spray. Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not taste or swallow. Do not handle or store near an open flame, heat or other sources of ignition. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may

explode.

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Storage: Keep container tightly closed until ready for use. Ground and bond metal

containers for liquid transfer to avoid static sparks.

shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Heptane, branched, cyclic and linear	400 ppm TWA 500 ppm STEL	500 ppm (2,000 mg/m3) PEL	None	None
2-Propanol	200 ppm TWA 400 ppm STEL	400 ppm (980 mg/m3) PEL	None	None
Ethyl acetate	400 ppm TWA	400 ppm (1,400 mg/m3) PEL	None	None
Xylenes	100 ppm TWA 150 ppm STEL	100 ppm (435 mg/m3) PEL	None	None
Toluene	20 ppm TWA	200 ppm TWA 300 ppm Ceiling 500 ppm MAX. CONC 10 minutes	None	None
Vinyl acetate	10 ppm TWA 15 ppm STEL	None	None	None

Engineering controls: Work should be done in an adequately ventilated area (i.e., ventilation

sufficient to maintain concentrations below one half of the PEL and other relevant standards). Local exhaust ventilation is recommended when general

ventilation is not sufficient to control airborne contamination.

Respiratory protection: Do not inhale vapors and fumes. Use NIOSH approved respirator if there is

potential to exceed exposure limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists.

Skin protection:Use impermeable gloves and protective clothing as necessary to prevent skin

contact. Safety showers and eye wash stations should be available.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid Color: Translucent Odor: Hydrocarbon-like Odor threshold: Not available. Not applicable pH: Vapor pressure: Not available. Boiling point/range: Not available. Melting point/ range: Not available.

Specific gravity: 0.82

Vapor density:Not available.Flash point:< -6.7 °C (< 19.94 °F) Setaflash Closed Cup</th>Flammable/Explosive limits - lower:1.1 % (Heptane, branched, cyclic and linear)Flammable/Explosive limits - upper:6.7 % (Heptane, branched, cyclic and linear)

Autoignition temperature:

Flammability:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

VOC content:

Not available.

Not available.

Not available.

Solubility in water:

Insoluble

Solubility in water:

Viscosity:

Not available.

Not available.

10. STABILITY AND REACTIVITY

Stability: Stable under recommended storage conditions.

None expected.

Hazardous reactions:

Irritating and toxic gases or fumes may be released during a fire. Oxides of carbon.

Hazardous decomposition

products:

Incompatible materials: Strong acids, alkalies and oxidizing agents.

Reactivity: This product may react with strong acids, bases and oxidizing agents.

Heat, flames, sparks and other sources of ignition. Take measures to prevent the build-up of

Conditions to avoid: electrostatic charges.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: Causes respiratory tract irritation. The solvent vapors can be harmful and cause headache,

nausea, and intoxication. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Chronic exposure to toluene may have effects on the central nervous system and these effects may progress to be irreversible. Intentional misuse of toluene has resulted in reproductive effects including physical and

developmental abnormalities.

Skin contact: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of

the skin. May cause allergic skin reaction in susceptible individuals.

Eye contact: Causes eye irritation. Prolonged eye contact may cause severe eye damage.

Ingestion: Not expected under normal conditions of use. May cause gastrointestinal tract irritation if

swallowed. Aspirated material can enter the lungs and result in pneumonitis. Ingestion of this product may result in central nervous system effects including headache, sleepiness, dizziness,

slurred speech and blurred vision.

Hazardous Component(s)	ardous Component(s) LD50s and LC50s	
Heptane, branched, cyclic and linear	None	Irritant, Central nervous system
2-Propanol	Oral LD50 (Rat) = 5,045 mg/kg Oral LD50 (Mouse) = 3,600 mg/kg Oral LD50 (Rabbit) = 6,410 mg/kg Oral LD50 (Rat) = 4.7 g/kg Oral LD50 (Mouse) = 4.5 g/kg Oral LD50 (Rabbit) = 8.0 g/kg Oral LD50 (Rabbit) = 5.03 g/kg Dermal LD50 (Rabbit) = 12,800 mg/kg	Allergen, Central nervous system, Irritant
Ethyl acetate	Oral LD50 (Rat) = 5.6 g/kg Oral LD50 (Mouse) = 0.44 g/kg	Blood, Central nervous system, Irritant
Xylenes	Oral LD50 (Mouse) = 1,590 mg/kg Oral LD50 (Rat) = 6,670 mg/kg Oral LD50 (Rat) = 3,523 - 8,600 mg/kg Oral LD50 (Mouse) = 5,627 mg/kg Oral LD50 (Rat) = 4,300 mg/kg Dermal LD50 (Rabbit) = > 43 g/kg Inhalation LC50 (Rat, 4 h) = 6,350 mg/l	Cardiac, Central nervous system, Irritant, Kidney, Liver
Toluene	Oral LD50 (Rat) = 2.6 g/kg Oral LD50 (Rat) = 5,000 mg/kg Dermal LD50 (Rabbit) = 12,124 mg/kg Inhalation LC50 (Rat, 4 h) = 8000 ppm	Behavioral, Cardiac, Central nervous system, Developmental, Ear, Irritant
Vinyl acetate	Oral LD50 (Rat) = 2,920 mg/kg Oral LD50 (Mouse) = 1,613 mg/kg Dermal LD50 (Rabbit) = 2,335 mg/kg Inhalation LC50 (Rat, 4 h) = 3680 ppm	Central nervous system, Irritant, Mutagen, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
			(Specifically Regulated)
Heptane, branched, cyclic and linear	No	No	No
2-Propanol	No	No	No
Ethyl acetate	No	No	No
Xylenes	No	No	No
Toluene	No	No	No
Vinyl acetate	No	Group 2B	No

12. ECOLOGICAL INFORMATION

Ecological information:

No specific studies have been conducted by Henkel on the ecotoxicity or environmental fate of this material; however, commonly available data on the

material indicate that uncontrolled releases to soil, ground water, or surface waters could entail acute and/or chronic ecological effects, depending on the quantity and concentration of such releases. Releases of volatile components to the atmosphere are not believed to entail significant ecological consequences provided such releases are within the exposure levels set forth in this document. Accordingly, all appropriate measures should be taken to avoid uncontrolled releases to the environment, and any spills or other uncontrolled releases which may occur should be contained and cleaned up immediately in accordance with Section 6.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Legal disposition of wastes is the responsibility of the owner/generator of the

waste. Applicable federal, state and/or local regulations must be followed during treatment, storage, or disposal of waste containing this product. Empty

containers must be handled with care due to product residue.

Hazardous waste number: D001: Ignitable.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:AdhesivesHazard class or division:3Identification number:UN 1133

Packing group:

DOT Hazardous Substance(s): Xylene (mixed), Toluene

International Air Transportation (ICAO/IATA)

Proper shipping name: Adhesives
Hazard class or division: 3
Identification number: UN 1133
Packing group: II

Water Transportation (IMO/IMDG)

Proper shipping name: ADHESIVES (Heptanes)

Hazard class or division: 3
Identification number: UN 1133
Packing group: II

Marine pollutant: Heptanes

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control

Act Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Fire, Immediate Health, Delayed Health

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements

of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Vinyl acetate (CAS# 108-05-4). Xylenes (CAS# 1330-20-7). Toluene

(CAS# 108-88-3). Ethylbenzene (CAS# 100-41-4).

CERCLA Reportable quantity: Xylenes (CAS# 1330-20-7) 100 lbs. (45.4 kg)
Toluene (CAS# 108-88-3) 1,000 lbs. (454 kg)

Heptane, branched, cyclic and linear (CAS# 426260-76-6)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or

other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2, 3, 8, 11, 15.

Prepared by: Product Safety and Regulatory Affairs

Issue date: 12/19/2017

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Davlyn LLC and its affiliates ("Davlyn") does not assume responsibility for any results obtained by persons over whose methods Davlyn has no control. It is the user's responsibility to determine the suitability of Davlyns products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Davlyn's products. In light of the foregoing, Davlyn specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Davlyn's products. Davlyn LLC further disclaims any liability for consequential or incidental damages of any kind, including lost profits.